Multimedia Speaker



SP-9700/SS-4697

Power (G Type) 2.0 Channel

SP-9700
P.M.P.O. 120W
RMS 1 W + 1 W
(2 Channel)

2.1 Channel

SS-4697
P.M.P.O. 440 W
RMS 5 W + 1 W x 2 + 0.25W x 2
(2.1 Channel)

SP-9700

Features

- 2 channel stereo Amplifier
- Magnetically Shielded
- Application on PC, CD-ROM, CD Player, Games, etc.

Specification

- Frequency Response : 100Hz~20KHz
- Impedance : 8 ohm
- Panel Controls : Power/Volume
- Drive Unit : Ø57mm Full Range Speaker
- Input Plug : Mini 3.5Ø Stereo Plug
- Power Supply : USB Bus Power
- Dimension (W x H x D) : 85 x 205 x 86 mm

SS-4697

Features

- 2.1 Channel Stereo Amplifier
- Magnetically Shielded
- Application on PC, CD-ROM, CD Player, Games, etc.

Specification

- Frequency Response : 80Hz~20KHz ; 250Hz/12dB/oct (Woofer)
- Impedance : Woofer 8 ohm, Sat 4/8 ohm
- Panel Controls : Power/Volume
- Drive Unit : Ø57mm+Ø27mm Full Range Speaker (SP-9700)
  3" Woofer Range Speaker (SW-4600)
- Input Plug : Mini 3.5Ø Stereo Plug
- Power Supply : AC in (A)
- Dimension (W x H x D) : 110 x 155 x 128 mm (SW-4600)
  85 x 205 x 86 mm (SP-9700)

Packing Information

	Packing	CUFT.	20FT	40FT	40HQ
SP-9700	30 Set/Ctn.	2.93'	10830	22530	25410
SS-4697	12 Set/Ctn.	3.11'	3948	8496	9468

Multimedia ready

Excellent frequency response

High power for your good music

Low distortion circuit

Magnetically shielded

All brand names and trademarks are the property of their respective owners.

KME 金橋電子 Group KEY MOUSE ELECTRONIC ENTERPRISE CO., LTD.
www.kmepc.com www.k-mex.com